

Total No. of Questions : 6]

SEAT No. :

P4669

[Total No. of Pages : 2

[4860] - 37

M.E. (Civil) (Structures)

ADVANCED DESIGN OF CONCRETE STRUCTURES

(2008 Pattern) (Semester - I) (Elective - I)

Time : 4 Hours]

[Max. Marks : 100

Instructions to the candidates:

- 1) Solve any two questions from each section.
- 2) Answers to the two sections should be written in separate answer books.
- 3) Neat diagrams must be drawn wherever necessary.
- 4) Figures to the right side indicate full marks.
- 5) Use of Calculator and relevant IS codes is allowed.
- 6) Assume suitable data if necessary.

SECTION - I

- Q1)** a) Draw yield lines for the following : **[10]**
- i) Triangular slab with fixed supports on two adjacent side with one side unsupported.
 - ii) Rectangular slab fixed at two adjacent sides, other two sides free and column at the corner at the junction of free sides.
 - iii) Circular slab with fixed support.
- b) Design a RCC slab for a circular hall of diameter 6m using Yield Line Theory. Assume the peripheral support thickness 300mm. The slab is simply supported. Use M20 Fe500 take Live load = 4 kN/m² & floor finish load = 1.2 kN/m². Draw reinforcement details. **[15]**
- Q2)** a) Design a grid slab for a floor of hall 15 × 18m c/c having square grid of 1.5m. Use M25 Fe415 take Live load = 5kN/m² and floor finish load = 1.5kN/m². Apply the required check & draw reinforcement details. **[15]**
- b) Design a flat slab for a hall with column spacing 6m × 6m c/c. The size of the column is 500 mm × 500 mm each. Use M20 Fe415 take Live load = 4kN/m² & floor finish load = 1.5kN/m². Draw reinforcement details. **[10]**

P.T.O.

- Q3)** Design a staging for circular type ESR for 2.5 lakh liters with staging height 10m using M25, Fe500 in earthquake zone III. Safe bearing capacity is 180 kN/m². Design of container is not required. Assume approximate dimension of container, wall, top, bottom slab thickness, beams sizes & number of columns. Design must include calculations of vertical loads and horizontal force calculations. Design the bracings, columns and foundations. Draw the reinforcement details. [25]

SECTION - II

- Q4)** Design deep beam of a hall for flexure and shear for the following : [25]

Clear span = 5m, width of support = 450mm, working UDL on the beam 1500kN/m. Take the total depth of beam = 3.5m. Use M40 & Fe500. Show all Analysis and Design calculations & draw the reinforcement details.

- Q5)** A two span prestressed concrete continuous beam ABC having cross section 300 × 750mm simply supported at A & C and continuous over B with M45 and multistrand cables 2 Nos 12T13 with $f_y = 1900 \text{ N/mm}^2$ stressed to 75% of f_y , each span is of 15m, superimposed load on both the spans 12kN/m, Assume 15% loss of prestress. [25]

- i) Determine primary secondary moment at support at prestress and dead load.
- ii) Calculate shift and stress in extreme fibers at working load.
- iii) Draw the resultant line of thrust at working load.

- Q6)** Design post tensioned prestressed concrete slab for a floor for the following Flat interior panel of 8m × 8m, live load on slab 4.5 kN/m², floor finish load on slab = 1kN/m², concrete grade M50HT steel is S3 cables of cross sectional area of each strand 150mm² with $f_y = 1900 \text{ N/mm}^2$. Design cables to serve as beams. Assume 3 panels in each direction (floor size 24m × 24m) width of the beam on periphery of floor 600mm and column size 600mm × 600mm. Design must include check fiber stresses in concrete and deflection. Draw sketches showing cable profiles. [25]

