Total No. of Questions: 10]	SEAT No.:	
D20#0	•	

P3059 [5059]-501 B.E (Civil)

[Total No. of Pages :3

ENVIRONMENTAL ENGINEERING-II (2012 Course) (Semester-I) (401001)

Time: 2½ Hours] [Max. Marks: 70

Instructions to the candidates:

- 1) Attempt Q.1 or Q.2, Q.3 or Q.4, Q.5 or Q.6, Q.7 or Q.8, and Q.9 or Q.10.
- 2) Figures to the right indicates full marks.
- 3) Draw Neat figures wherever necessary.
- 4) Assume suitable data if necessary.
- 5) Use of scientific calculators is allowed.
- Q1) a) Define treatability index. Write wastewater treatment option with respect to treatability index.[4]
 - b) Write the procedure to determine total volatile solids and its significance in wastewater treatment. .[6]

OR

- Q2) a) Explain pumping of sewage with respect to need, location and types of pumps.[5]
 - b) Design a mechanically cleaned radial flow circular settling tank for treating sewage from a population of 25000 persons. [5]

Given:

Maximum hourly flow = (1/14) of the daily flow

Volume of sludge = 1.19 1/c/d

Water consumption = 135 1/c/d

- **Q3)** a) Write the difference between preliminary treatment and primary treatment.[5]
 - b) Write a short note on the self-purification of streams. [5]

OR

	following data [6]		
	i)	Flow	$= 2.30 \mathrm{m}^3/\mathrm{min}$
	ii)	BOD_5	= 300 mg/1
	iii)	Volume of filter 1	$= 900 \text{ m}^3$
	iv)	Volume of filter 2	$= 900 \text{ m}^3$
	v)	Filter depth	= 2 m
	vi)	Recirculation ratio for both the filter	= 1.5
	Use	NRC formula.	
b)	With the help of a neat sketch, explain the activated sludge process. [4]		
Q5) a)	What do you understand by oxidation pond? Where it is used? What is its principle? [8]		
b)	Explain aerated lagoon with respect to its working principle, design parameters and applications. [8]		
		OR	
Q6) a)	Write short note on phytoremediation for wastewater treatment. [8]		
b)	Design an oxidation pond for a colony of 3000 population. The sewage flow is $1001/p/d$. BOD ₅ is 300 mg/1 . Assume necessary required data. [8]		
Q7) a)	Design a sludge digestion tank with the following data		wing data [8]
	i)	Average flow of sewage	= 60 MLD
	ii)	Total suspended solids in raw sewage	$= 350 \mathrm{mg/1}$
	iii)	Volatile suspended solids	$= 250 \mathrm{mg/1}$
	iv)	Moisture content in the digested sludge	= 87 %
	v)	Removal from PST	= 65 %
	vi)	Moisture content in fresh sludge	= 95 %

Q4) a) Calculate the effluent BOD of a two stage trickling filter with the

b) Draw a flowchart of package sewage treatment plant and explain its working principle. Write its advantages and disadvantages. [8]

OR

- **Q8)** a) Design a gravity thickeners for thickening the combined primary and activated sludge from a treatment plant for 150000 population. [8]
 - b) Write working principle of UASB. Enlist design parameters of UASB and its limitations. [8]
- **Q9)** a) Enlist different units used in preliminary, primary and secondary treatment in industrial wastewater treatment. Write its significance for which impurities to be removed. [9]
 - b) Explain equalization and neutralization unit process with respect to its working principle, need, factors affecting the process and application. [9]

OR

- Q10)a) Draw a neat sketch showing the points where spent wash is generated in the distillery.[6]
 - b) Discuss the characteristics of dairy industry. [4]
 - c) Draw a flow chart showing various treatment units used to treat sugar industry wastewater. Explain the important units. [8]

✓ ✓ ✓