Marking Scheme
Total No. of Printed Pages - 5

Total No. of Questions - [5]

G.R. No.	77		

Paper Code: - U117-105A (RE-FF8F)

DECEMBER 2017 / ENDSEM RF-EXAM

F. Y. B. TECH. (COMMON) (SEMESTER - I)

COURSE NAME: ENGINEERING PHYSICS

COURSE CODE: ES10175A

(2017 PATTERN)

Time: [2 Hours]

[Max. Marks: 50]

Instructions to candidates:

- 1) Answer Q.1 OR Q.2, Q.3 OR Q.4 and Q.5
- 2) Figures to the right indicate full marks.
- 3) Use of scientific calculator is allowed
- 4) Use suitable data wherever required

Q. N	0.	Question	M	Marks distribution	Difficulty	Cognitive	(
Q.1)	a)	Explain the construction and working of carbon dioxide laser with the help of energy level diagram.	[6]	Construction: 2M, Working with energy level diagram: 4M	M	Compre- hension	5
	b)	Explain : i) Stimulated emission ii) Pumping ii) Optical cavity	[6]	2M each	M	Compre- hension	5
	c)	Find the relative population of the two states in a He-Ne laser that produces light of wavelength 6328 Å at 300 K and 600 K. Comment on answer obtained at two different temperatures.	[4]	At T = 300 K and 600 K: 1.5M each. $\frac{N_2}{N_1} = e^{\frac{-(E_2 - E_1)}{KT}}$ At T= 300K, Ans- 1.04×10 ⁻³³ and T=600K, 3.17×10 ⁻¹⁷ Comment: 1M	M	Appli- cation	5
		OR			14.3	1. A.	100
Q.2)	a)	Enumerate the applications of laser biomedical field and explain any one in detail.	[6]	Enumerate: 2M Any one in detail: 4M	M	Compre- hension	:
	b)	Explain the construction and working of single hetero junction diode laser with suitable energy band diagram.	[6]	Construction: 2M Working with energy level diagram: 4M	M	Compre- hension	4.
	c)	The refractive index of core and cladding of an optical fibre are 1.64 and 1.58, respectively. Calculate its numerical aperture and maximum acceptance angle.	[4]	$NA = \sqrt{n_1^2 - n_2^2}$ $= \sqrt{1.64^2 - 1.58^2}$ $= 0.4396$	М	Appli- cation	4

				$\sin \theta_0 = NA = 0.4396$			
				$\therefore \theta_0 = \sin^{-1}(0.4396) = 26.7 \text{de}$			
Q.3)	a)	Derive Schrodinger's time independent equation for a matter wave.	[6]	Define MW: 1M Derivation: 5M	M	Compre- hension	6
	b)	What is reactor poisoning? How is nuclear fission reaction rate maintained in spite of reactor poisoning?	[4]	Reactor poisoning: 3M Remedies: 1M	Н	Compre- hension	6
	0)	When a slow neutron is captured by U ²³⁵ nucleus, fission results in the release of 200 MeV energy. If the output power of a nuclear reactor is 1.6 MW, calculate the number of nuclei undergoing fission per second.	[4]	E = 200 MeV = 3.2×10^{-11} J Power of rector = 1.6 MW= 1.6×10^6 J/sec No. of nuclei = $(1.6 \times 10^6)/(3.2 \times 10^{-11})$ = 5×10^{16}	M	Appli- cation	6
	Tan y	OR					6
Q.4)	a)	Explain the building blocks of Nuclear reactor with the help of a diagram.	[6]	Diagram: 2M Explanation : 4M	M	Compre- hension	6
	b)	Discuss with the help of liquid drop model, why nuclear fission takes place in U ²³⁵ , but not in U ²³⁸ ? Also draw an appropriate diagram.	[4]	Diagram: 1M Explanation: 3M	Н	Compre- hension	6
	c)	An infinite potential well has a width of 1 Å. What is the fractional change in the lowest two permissible energies of an electron in this well if the width is increased to 2 Å? (Given: $h = 6.63 \times 10^{-34}$ J-sec, $m = 9.1 \times 10^{-31}$ kg)	[4]	E= $(n^2h^2)/(8mL^2)$ For L = 1 Å, E ₁ = 37.7 eV, E ₂ = 150.8 eV For L = 2 Å, E ₁ = 9.43 eV E ₂ = 37.7 eV Δ E ₁ = 28.27 eV, Δ E ₂ = 113.1 eV, 2M each	M	Application	6
Q.5)		Attempt following multiple choice questions: [1x20=20 marks]				No. 1	5
	a)	As the audience increases in a concert hall, the reverberation time	[1]	ii 	М	Compre- hension	1
		i. remains constant ii. decreases iii. increases iv. initially increases and then decreases					
	b)	Intensity level corresponding to threshold intensity on dB scale is i. 1 iii12 iii. 0 iv. 12	[1]	iii	M	Appli- cation	1

(c)	The sound waves that propagate in a meal bar may be	[1]	iii	M	Compre- hension	1
d)	A sound wave of wavelength 5 cm traveling with a speed of 340 m/s has a time period of	[1]	iv	M	Appli- cation	1
e)	Principle of ultrasound echo sounding is used in i. depth sounding ii. cleaning iii. welding iv. drilling	[1]		M	Appli- cation	1
f)	For a thin uniform film, the interference pattern by reflection consists ofi. Uniform intensity throughout the film ii. Straight parallel bands of equal width iii. Straight parallel bands of unequal width iv. Curved bands	[1]		M	Compre- hension	2
g)	The first minimum for a Fraunhofer diffraction from a single slit (width a) occurs at an angle θ with respect to the incident beam (wavelength λ) such that $\theta = \frac{1}{1000}$ i. $\sin^{-1}(\lambda/a)$ iii. $\sin^{-1}(a/\lambda)$ iii. π iv. $\pi/2$	[1]		L	Compre- hension	2
h)	For a diffraction grating with a grating element 1.67×10^{-4} cm illuminated by light of wavelength $\lambda = 6328$ Å, the maximum order observed is i. 4 ii. 1 iii. 2 iv. 2.6	[1]	III	M	Appli- cation	2
i)	A wedge shaped film is formed by keeping a separator of thickness t between two glass plates. If a separator is moved away from the angle of wedge, fringes will i. come close to one another ii. move away from one another iii. remains as it is iv. first comes close and then moves	[1]		M	Comprehension	2

	away					
j	What should be the thickness of non-reflecting coating on glass if μ _{glass} = 1.5 and μ _{film} = 1.25 and λ = 6000Å? i. 0.2 μm ii. 0.3 μm iii. 1 μm iv. 0.12 μm	[1]	iv	M	Appli- cation	2
	i. close to conduction band iii. at the center of band gap iv. within valence band	[1]	ii	M	Compre- hension	3
1	Fermi-Dirac function value at room temperature for E < E _F i. f(E) < 1 ii. f(E) > 1 iii. f(E) = 1 iv. f(E) = 0	[1]		M	Compre- hension	3
n Name	Resistance of semiconductor i. Increases ii. remains unaffected iii. decreases iv. none of these	[1]	iii	L	Compre- hension	3
n	Current in a p-n junction diode for forward biasing. i. decreases exponentially ii. is linear iii. is unaffected by biasing iv. increases exponentially	[1]	iv	M	Comprehension	3
0	For a n-type semiconductor if the doping concentration of donor impurity is 1.8 × 10 ¹⁵ /cm ³ and intrinsic charge carriers concentration is 10 ¹⁰ /cm ³ at 300K. Then what is the concentration of minority charge carriers? a) 0.55 × 10 ⁻⁵ /cm ³ b) 0.55 × 10 ⁻⁵ /m ³ c) 0.56 × 10 ⁵ /cm ³ d) 0.56 × 10 ⁵ /m ³	[1]	c	M	Appli- cation	3

, P.	When the two solar cell are connected in parallel i. current increases ii. voltage decreases iii. current decreases iv. voltage increases	[13]		L	Compre- hension	4
q)	In a solar cell, due to internal resistance R, which is in series with load resistance i. current drops ii. voltage drops iii. efficiency increases iv. fill factor increases	[1]	ii	M	Comprehension	4
r)	For a solar cell with short circuit current 3.3 A, open circuit voltage 0.614 and fill factor 75%, what is the maximum power generated? i. 1.52 W ii. 0.152 W iii. 15.2 W iv. 0.0152 W	[1]		M	Appli- cation	4
s)	To avoid hot spotting in solar panel i) blocking diode is connected in series to each cell ii) bypass diode is connected in series to each cell iii) blocking diode is connected in parallel to each cell iv) bypass diode is connected in parallel to each cell	[1]		M	Comprehension	4
t)	Find out the maximum wavelength above which silicon is transparent? (Given: Band gap of Silicon = 1.1 eV, h= 6.63 × 10 ⁻³⁴ J-sec, c = 3 × 10 ⁸ m/s) i) 1125 Å ii) 11250 Å iii) 11250 Å	[1]		M	Appli- cation	4