Total No. of Questions—8]

[Total No. of Printed Pages—3

Seat No.

[5152]-520

## S.E. (Mechanical, Mech. Sandwich and Automobile) (II Sem.) EXAMINATION, 2017 ELECTRICAL AND ELECTRONICS ENGINEERING (2015 PATTERN)

Time: Two Hours

Maximum Marks: 50

- N.B. :— (i) Attempt Q. No. 1 or Q. No. 2, Q. No. 3 or Q. No. 4, Q. No. 5 or Q. No. 6, Q. No. 7 or Q. No. 8.
  - (ii) Neat diagrams must be drawn wherever necessary.
  - (iii) Figures to the right indicate full marks.
  - (iv) Assume suitable data, if necessary.
- 1. (a) The power input to 500 V, 50 Hz, 6 pole, 3-phase induction motor running at 975 rpm is 40 kW. The stator losses are 1 kW and friction and windage losses are 2 kW. Calculate:
  - (i) slip
  - (ii) rotor copper losses and
  - (iii) efficiency of motor.

[6]

(b) Why is a starter necessary for operating DC motors? Draw neat diagram of three point starter for DC shunt motor and explain the working. Write the function of no-volt coil and overload release. [7]

P.T.O.

- 2. (a) Differentiate between slip ring and squirrel cage induction motor. [6]
  - (b) A 250 V DC shunt motor has an armature resistance of 0.5 ohm and field resistance of 125 ohm. It drives a load at 1000 rpm and takes a current of 25 A. The field circuit resistance is then increased to 150 ohm. Calculate new speed assuming load torque to be constant. [7]
- **3.** (a) Write any six important features of ATmega 328P microcontroller. [6]
  - (b) Elaborate the construction of variable reluctance stepper motor with the help of suitable sketches and hence explain its Full-step and Half-step modes of operations. [6]

Or

- **4.** (a) Describe the constructional details and operation of shaded pole induction motor with the help of appropriate diagrams. [6]
  - (b) Draw bit pattern of status register of ATmega 328P and explain the significance of all bits. [6]
- 5. (a) Explain various timers in ATmega 328 microcontroller. [6]
  - (b) Explain the interfacing of LED with Arduino board with required functions and write an algorithm to blink an LED. [6]

<b>6.</b> (a)	Explain the following Arduino functions used for serial
	communication:
	(i) Serial.begin()
	(ii) Serial.end( )
	(iii) Serial.available( ). [6]
<i>(b)</i>	
( <i>b</i> )	Draw interfacing circuit diagram of Arduino board and LCD.
	Also write basic algorithm used for this interfacing. [6]
<b>7.</b> (a)	List any six features of in-built ADC in ATmega 328P
1 /x	microcontroller. [6]
<i>(b)</i>	Explain temperature measurement scheme using LM35
	temperature sensor and ATmega 328P microcontroller with the
	help of interfacing diagram. [7]
	Or
<b>9</b> (a)	29.
<b>8.</b> (a)	Explain the format of ADCSRB and DIDRO registers mentioning
	the function of each bit. [6]
<i>(b)</i>	Draw and explain the interfacing diagram of ATmega
_	328P microcontroller to control operation of DC motor
Color - The state of the s</th <th>using PWM. [7]</th>	using PWM. [7]
	328P microcontroller to control operation of DC motor using PWM. [7]
	Ox V
[5159] 590	3
[5152]-520	<b>3</b>
	· · · · · · · · · · · · · · · · · · ·